



Spars, Rigging, and Hardware for Sailboats

Rig-Rite, Inc.

Phone: (001) 401-739-1140 -- FAX: (001) 401-739-1149

www.RigRite.com [Ordering/Questions](#)

Gooseneck Slides

Gooseneck Slides

Gooseneck Slides are used to allow easy adjustment of the Boom height, and either fit into an integral Track extruded in the Mast Section, or to a separate Track mounted on the Mast. On smaller boats use of a Gooseneck Slide will obviate the need for a Halyard Winch, by allowing use of a rope tackle to tension the sail luff once the Halyard is cleated. All Gooseneck Slides incorporate provisions for attachment of a downhaul line or shackle, or a pin stop to lock it into place on the Track. **Gooseneck Slides are listed here by the Type and size of the Track** they slide in or on, Special **Proctor Spars** Gooseneck Slides and Slide Assemblies are listed separately.

Rig-Rite stocks a large variety of Gooseneck Slides originally produced by many different Spar Builders. **To determine which Gooseneck Slide you need, you must know the size of the Groove or Track it is to fit, and the Pin Size & Height of the Toggle it attaches to.** As always, there have been many 'specials' produced over the years, if a Gooseneck Slide you need is not listed here, please contact us with complete dimensions.

For Toggles compatible with the Gooseneck Slides listed here (and others), See [Gooseneck Toggles](#).

[Gooseneck Slides for Internal Boltrope Groove](#)

[Gooseneck Slides for Internal Flat Track](#)

[External Track Gooseneck Slides](#)

[Special Gooseneck Slides](#)

[Proctor Gooseneck Slides](#)

Gooseneck Slides for Internal Boltrope Groove

Standard SS Gooseneck Slide for Boltrope & 3/4" Toggle: K-9138A:

SS Gooseneck Slide designed for use with the standard Kenyon 3/4"

Toggle, [K-9267](#). Slide fits Kenyon B, D, E, 3049, and 3650 Mast Sections,

and other Mast Sections with a boltrope groove that is 9/16" ID or larger. Slide has welded SS ring for downhaul attachment and includes 1/4" pin for Toggle attachment. Slide is 2 1/2" long x (maximum) 5/8" wide.




K-9138A

Special SS Gooseneck Slide for Small Boltrope & 3/4" Toggle: K-9138-SA:

Special SS Gooseneck Slide designed for use with the standard Kenyon 3/4" Toggle, [K-9267](#), and Mast Sections with **smaller** boltrope grooves. Slide fits Kenyon A, C-1, C-6, 2331, and MORC Mast Sections, and other Mast Sections with a boltrope groove that is 1/2" ID or smaller. Slide has welded SS ring for downhaul attachment and includes 1/4" pin for Toggle attachment. Slide is 2 1/2" long x (maximum) 5/8" wide. #

Standard SS Gooseneck Slide for Large Boltrope & 1" Toggle: K-1685A:

SS Gooseneck Slide designed for use with the standard Kenyon 1" Toggle, [K-1993](#). Slide fits Kenyon B, D, E, 3049, and 3650 Mast Sections, and other Mast Sections with a boltrope groove that is 9/16" ID or larger. Slide has heavy welded SS ring for downhaul attachment and includes 1/4" bolt and locknut for Toggle attachment. Slide is 3" long x 1" (maximum) wide.



Special SS Gooseneck Slide for Small Boltrope & 1" Toggle: K-10331A:

Special SS Gooseneck Slide designed for use with the standard Kenyon 1" Toggle, [K-1993](#), and Mast Sections with **smaller** boltrope grooves. Slide fits Kenyon A, C-1, C-6, 2331, and MORC Mast Sections, and other Mast Sections with a boltrope groove that is 1/2" ID or smaller. Slide has heavy welded SS ring for downhaul attachment and includes 1/4" bolt and locknut for Toggle attachment. Slide is 3" long x 1" (maximum) wide.



K-10331A

Gooseneck Slide for Large Boltrope & 1 1/2" Toggle: K-1685-1A:

SS Gooseneck Slide specially designed for use with Kenyon [K-10518-series](#) Gooseneck Toggle/Tack Assemblies. Slide fits Kenyon B, D, E, 3049, and 3650 Mast Sections, and other Mast Sections with a boltrope groove that is 9/16" ID or larger. Slide has heavy welded SS ring for attachment of downhaul line or shackle and includes vertical bolt and locknut. SS Gooseneck Slide is 3" high x 1" (maximum) wide and fits most 1 1/2" Toggles using a **1/4" vertical pin**.



K-1685-1A

Special Gooseneck Slide for Small Boltrope & 1 1/2" Toggle: K-10331-1A:

Special SS Gooseneck Slide specially designed for use with Kenyon [K-10518-series](#) Gooseneck Toggle/Tack Assemblies, and Mast Sections with

smaller boltrope grooves. Slide fits Kenyon A, C-1, C-6, 2331, and MORC Mast Sections, and other Mast Sections with a boltrope groove that is 1/2" ID or smaller. Slide has heavy welded SS ring for attachment of downhaul line or shackle and includes vertical bolt and locknut. SS Gooseneck Slide is 3" high x 1" (maximum) wide and fits most 1 1/2" Toggles using a **1/4" vertical pin**.

Special Gooseneck Slide for Boltrope & 1 1/2" Toggle: PP-M5A:

Special Extruded Aluminum Gooseneck Slide fits [RR-4025 Mast Section](#), and a few other Teardrop-shaped mast sections with a 1/2" boltrope groove. Aft side has 1 5/8" cutout for Gooseneck Toggle, [PP-B4](#), and others, and features 1/4" hole for downhaul line or shackle. Gooseneck Slide is 3" high x 5/8" wide and includes **1/4" vertical pin**, locknut, and nylon washers to eliminate chafe against Toggle. **Special, as used on Pearson 22, Ensign, Electra**, and a variety of others.



Bronze Gooseneck Slide for Boltrope & 2 1/4" Toggle w/ 1/2" Pin: Fam 1304:

Chrome Bronze Gooseneck Slide for Boltrope & 2 1/4" Toggle w/ 1/2" Pin: Fam 1304C:

Cast Bronze Gooseneck Slide was designed for use with special Famet Tubular Gooseneck Toggles, [Fam 1205T & 1206T](#), but also accepts a variety of Gooseneck Toggles up to 2 1/4" high with a **1/2" clevis pin**. Slide fits all Mast Sections with a boltrope groove that is 9/16" ID or larger. Slide has 5/16" hole for downhaul attachment and is 3 1/4" long x (maximum) 15/16" wide. Used with **Nicro-Fico** standard and Roller-Reefing Goosenecks.

Gooseneck Slides for Internal Flat Track

Gooseneck Slide for 3/4" Internal Flat Track & 1 1/2" Toggle w/ 1/4" Pin: PP-M6A:

Machined Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4" high x 11/16" wide and attaches to Toggle using a **1/4" vertical bolt**. Aft side has 1 5/8" cutout for Gooseneck Toggle, [PP-B4](#), and others, and features 5/16" hole for downhaul line or shackle. Includes vertical SS bolt, locknut, and nylon washers to eliminate chafe against Toggle. **As used on Bristol 22, 24, Pearson 26** and others. *



Gooseneck Slide for 3/4" Internal Flat Track & 1 1/2" Toggle w/ 5/16" Pin: PP-M7A:

Machined Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4" high x 11/16" wide and attaches to Toggle using a **5/16" vertical bolt**. Aft side has 1 5/8" cutout for

Gooseneck Toggle, and features 5/16" hole for downhaul line or shackle. Includes vertical SS bolt, locknut, and nylon washers to eliminate chafe against Toggle.

Gooseneck Slide for 3/4" Internal Flat Track & 2 3/8" Toggle w/ 5/16" Pin: PP-M7-25F:

Machined Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4 3/4" high x 1 1/16" wide and attaches to Toggle using a **5/16" vertical Pin**. Aft side has 2 1/2" cutout for Gooseneck Toggle, and features 5/16" hole for downhaul line or shackle. Includes 5/16" vertical Pin and nylon washers to eliminate chafe against Toggle. NR, Fam 1302+1/8 WR mm

Gooseneck Slide for 3/4" Internal Flat Track & 1 1/2" Toggle w/ 3/8" Pin: PP-M8-6V:

Cast Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 5" high x (maximum) 1" wide and attaches to Toggle using a **3/8" vertical threaded Pin**. Aft side has 1 9/16" cutout for Gooseneck Toggle, and features 7/16" hole for downhaul line or shackle. Includes vertical SS threaded Pin. Originally used with **Vassen** standard and Roller-Reefing Goosenecks made in Holland in the 1960's. 66.52.14



PP-M8-6V

SS Gooseneck Slide for 3/4" Internal Flat Track & 2 1/16" Toggle w/ 3/8" Pin: PP-M8-6S:

Cast, welded SS Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 3 3/4" high x (maximum) 7/8" wide and attaches to Toggle using a **3/8" vertical bolt**. Aft side has 2 1/8" cutout for Gooseneck Toggle, and features welded SS ring with 5/16" hole for downhaul line or shackle. Includes vertical SS bolt, locknut, and nylon washers to eliminate chafe against Toggle. Sch* .18T,1 3/8L,H@7/8



PP-M8-6S

Gooseneck Slide for 3/4" Internal Flat Track & 2 1/4" Toggle w/ 3/8" Pin: PP-M8A:

Machined Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4 3/4" high x 1 1/16" wide and attaches to Toggle using a **3/8" vertical bolt**. Aft side has 2 1/4" cutout for Gooseneck Toggle, and features 5/16" hole for downhaul line or shackle.

Includes vertical SS bolt, locknut, and nylon washers to eliminate chafe against Toggle. WR mm



PP-M8A

Gooseneck Slide for 3/4" Internal Flat Track & 2 1/4" Toggle w/ 3/8" Pin: Fam 1302SR-6:

Cast Bronze Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4 5/8" high x 1" (maximum) wide and uses a **3/8" vertical pin**. Aft side has 2 5/16" cutout for Gooseneck Toggle, and features 1/2" hole for downhaul line or shackle. This Slide is used with a variety of vertical pin arrangements, so no vertical pin is included.

Gooseneck Slide for 3/4" Internal Flat Track & 2 1/4" Toggle w/ 1/2" Pin: Fam 1302SR:

Cast Bronze Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 4 5/8" high x 1" (maximum) wide and uses a **1/2" vertical pin**. Aft side has 2 5/16" cutout for Gooseneck Toggle, and features 1/2" hole for downhaul line or shackle. This Slide is used with a variety of vertical pin arrangements, so no vertical pin is included.

Replaces original cast Aluminum version. As used on **Bristol 29.9**, and **Bristol 32** with a special Tack bolt arrangement and RR Gooseneck Toggle, [RR-45-67C](#). *Spec BZ rep.



Fam 1302

Gooseneck Slide for 3/4" Internal Flat Track & 2 3/8" Toggle w/ 1/2" Pin: PP-M8A-8:

Machined Aluminum Gooseneck Slide fits most Mast Sections with a 3/4" flat internal track. Gooseneck Slide is 5 7/8" high x 7/8" (.865") wide and uses a **1/2" vertical pin**. Aft side has 2 7/16" cutout for Gooseneck Toggle, and features 1/2" hole for downhaul line or shackle. Includes 1/2" Vertical Pin and nylon washers to eliminate chafe against Toggle. As used on MetalMast **MM7244** (and other Mast Sections with a 3/4" flat internal track) on a variety of boats, including **some Tartan 30's**, and others.



Gooseneck Slide for 7/8" Internal Flat Track & 2 3/8" Toggle w/ 1/2" Pin: PP-M9A:

Aluminum Gooseneck Slide has special configuration to fit all Mast

Sections with a 7/8" or 15/16" flat internal track. Gooseneck Slide is 5 7/8" high x 7/8" (.865") wide and uses a **1/2" vertical pin**. Aft side has 2 7/16" cutout for Gooseneck Toggle, and features 1/2" hole for downhaul line or shackle. Includes 1/2" Vertical Pin and nylon washers to eliminate chafe against Toggle. As used on Sound Spar **SS7747T** (and other Mast Sections with a 7/8" or 15/16" flat internal track) on a variety of boats, including **Allied Chance 3030, some Tartan 30's**, and others. Replaces earlier Cast version.



SS Gooseneck Slide for 7/8" Internal Flat Track & 2 3/8" Toggle w/ 1/2" Pin: PP-M9CS:

SS Gooseneck Slide to fit Mast Sections with a 7/8" flat internal track. Unique design allows use with Toggles fitting inside or outside of ears, unit has no provisions for downhaul attachment. Aft side ears allows use with a Toggle up to 1 3/4" high (between ears), or a Gooseneck Toggle with a 2 5/8" cutout (fitting outside of the ears). Cast Stainless Steel Gooseneck Slide is 4" high x 1 1/4" (maximum) wide and uses a **1/2" vertical pin**. This Slide is used with a variety of vertical pin arrangements, so no vertical pin is included. ca

SS Gooseneck Slide for 1" Internal Flat Track & 2 3/8" Toggle w/ 1/2" Pin: PP-M10CS:

SS Gooseneck Slide to fit Mast Sections with a 1" flat internal track. Unique design allows use with Toggles fitting inside or outside of ears, unit has no provisions for downhaul attachment. Aft side ears allows use with a Toggle up to 1 3/4" high (between ears), or a Gooseneck Toggle with a 2 5/8" cutout (fitting outside of the ears). Slide features (2) 1/4" screw holes for use when fixed installation is required. Cast Stainless Steel Gooseneck Slide is 4" high x 1 1/4" (maximum) wide and uses a **1/2" vertical pin**. This Slide is used with a variety of vertical pin arrangements, so no vertical pin is included. ca

Bronze Gooseneck Slide for 1" Internal Flat Track & 2 3/8" Toggle w/ 1/2" Pin: Fam 89-3TN:

Cast Bronze Gooseneck Slide to fit Mast Sections with a 1" flat internal track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a **1/2" SS clevis pin** (included). Slide has integral loop for downhaul attachment and is 6" high x 1 3/8" wide. Used with Famet standard and Roller-Reefing Goosenecks.

External Track Gooseneck Slides

SS Slide & Gooseneck Ass'y for 5/8" Sailtrack & 5/8" Boom: Sch 89-30X:

SS Gooseneck Slide Assembly for 5/8" (11/16" wide) Sailtrack (or 5/8" Aluminum Gooseneck Slide Track) and 5/8" wide Boom. Formed SS strap is 3 3/4" long x 1/2" wide, and attaches to 5/8" wide wood "T" Boom with (2) #10 (3/16") screws and nuts. Slide is 1 13/16" long, fits 5/8" Sail Track, and features captive SS Thumbscrew to allow for quick Boom height adjustment. **As used on El Toro.**

SS Gooseneck Slide for 5/8" Sailtrack & 3/4" Toggle: Ken K-1684-5:

SS Gooseneck Slide for 5/8" (11/16" wide) Sailtrack (or 5/8" Aluminum Gooseneck Slide Track) fits any gooseneck assembly using the standard Kenyon 3/4" Toggle, [K-9267](#), with a 1/4" pin (included). Slide has 3/8" hole for downhaul attachment **and** a SS Thumbscrew to allow for quick Boom height adjustment. Slide is 4" long x 7/8" wide and fits 5/8" Sail Track. **As used on Explorer, Pintail, and others.** ##r

**K-1684-5*****SS Gooseneck Slide for 7/8" Sailtrack & 3/4" Toggle: Ken K-1684-7:***

SS Gooseneck Slide for 7/8" Sailtrack fits any gooseneck assembly using the standard Kenyon 3/4" Toggle, [K-9267](#), with a 1/4" bolt and locknut (included). Slide has welded eye for downhaul attachment **and** a SS Thumbscrew to allow for quick Boom height adjustment. Slide is 4" long x 1 1/8" wide and fits 7/8" Sail Track. ##r

SS Gooseneck Slide for 7/8" x 1/8" Flat Track & 1" Toggle: K-1686A:

SS Gooseneck Slide for 7/8" x 1/8" SS Flat Track fits any gooseneck assembly using the standard Kenyon 1" Toggle, [K-1993](#), with a 1/4" bolt and locknut (included). Slide has heavy welded SS ring for downhaul attachment. Slide is 3" long x 1 1/16" wide and fits 7/8" x 1/8" SS Flat Track.

**K-1686A*****Bronze Gooseneck Slide for 7/8" x 1/8" Flat Track & 2 3/8" Toggle w/ 1/2" Pin: Fam 1305-8A:***

Bronze Gooseneck Slide fits 7/8" x 1/8" SS Flat Track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a 1/2" SS clevis pin (included). Slide has integral loop for downhaul attachment and is 4 1/2" long x 1 7/16" wide. Used with Famet standard and Roller-Reefing Goosenecks.

Gooseneck Slide for 15/16" x 1/4" T-Track & Special 5/8" Pin: Bart 89-1516S:

Special Chrome Bronze Gooseneck Slide for 15/16" x 1/4" T-Track fits Special 5/8" vertical gooseneck Toggle Bolt. Slide has 5/8" ID x 1 1/2" long vertical Tube for attachment to Special vertical gooseneck Toggle Bolt used with some Barton and Tupfitting Gooseneck assemblies. Slide is 3 1/4" long x 1 1/4" wide and includes thumbscrew for positive positioning on Track. Special Plastic Gooseneck T-Track, ***Bart 89-1516T***, is also available in 15" lengths. **As used on Grampian 26; Mirage 26, 27; Tanzer 22, and others.**

**Bart 89-1516S*****SS Gooseneck Slide for 1" x 1/8" Flat Track & 3/4" Toggle: RR-89-4TN:***

SS Gooseneck Slide for 1" x 1/8" SS Flat Track fits Rig-Rite 3/4" gooseneck Toggle with a **1/4" bolt** and locknut (included). Slide has heavy welded SS ring for downhaul attachment. Slide is 3" long x 1 1/8" wide and fits 1" x 1/8" SS Flat Track. **As used on some O'Day 27's.**

SS Gooseneck Slide w/ Spring Pin for 1" x 1/8" Flat Track & 3/4" Toggle: PP-M10SA:

SS Gooseneck Slide with Spring Pin fits 1" x 1/8" SS Flat Track *and* standard 1" aluminum T-Track. Slide fits special 3/4" Gooseneck Toggle ([Sch-45-S0404](#)) with a **1/4" SS clevis pin** (included). SS Spring Pin allows for quick and positive Boom height adjustment in track stop holes. Slide is 3" long x 1 1/4" wide and fits 1" x 1/8" Flat Track. **As used on Pearson 365 and 424 Mizzen masts, and others.**

***SS Gooseneck Slide for 1" x 1/8" Flat Track & 1" Toggle w/ 1/4" Pin: K-1687XS:***

Special SS Gooseneck Slide for 1" x 1/8" SS Flat Track (*and* standard 1" aluminum T-Track), fits any gooseneck assembly using the standard Kenyon 1" Toggle, [K-1993](#), with a **1/4" bolt** and locknut (included). Slide has heavy welded SS ring for downhaul attachment. SS Slide is 3" long x 1 1/8" wide. Available on Special order. **As used on some Cal 25's.** 67881

SS Gooseneck Slide for 1" x 1/8" Flat Track & 1 1/2" Toggle w/ 1/4" Pin: K-1687XL:

Special SS Gooseneck Slide specially designed for use with Kenyon [K-10518-series](#) Gooseneck Toggle/Tack Assemblies. Slide fits standard 1" x 1/8" T-Track or SS Flat Track. SS Gooseneck Slide is 3" high x (maximum) 1 1/8" wide and fits most 1 1/2" Toggles using a **1/4" vertical pin**. Slide has heavy welded SS ring for attachment of downhaul line or shackle and includes vertical bolt and locknut. Available on Special order.

Bronze Gooseneck Slide for 1" x 1/8" Flat Track & 2 3/8" Toggle w/ 5/16" Pin: NF 10326-5A:

Chromed Bronze Gooseneck Slide fits 1" x 1/8" SS or Bronze Flat Track and standard 1" aluminum T-Track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a **5/16" SS clevis pin** (included). Slide has integral loop for downhaul attachment and is 4" long x 1 7/8" wide. Used with Nicro-Fico standard and Roller-Reefing Goosenecks. NM-320-5

Bronze Gooseneck Slide for 1" x 1/8" Flat Track & 2 3/8" Toggle w/ 1/2" Pin: NF 10326-8A:

Chromed Bronze Gooseneck Slide fits 1" x 1/8" SS or Bronze Flat Track and standard 1" aluminum T-Track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a **1/2" SS clevis pin** (included). Slide has integral loop for downhaul attachment and is 4" long x 1 7/8" wide. Used with Nicro-Fico standard and Roller-Reefing Goosenecks. NM-320-8

SS Gooseneck Slide for 1 1/4" x 3/16" Flat Track & 1" Toggle: K-1065:

SS Gooseneck Slide for 1 1/4" x 3/16" SS Flat Track (and standard 1 1/4" aluminum T-Track), fits any gooseneck assembly using the standard Kenyon 1" Toggle, [K-1993](#), with a **1/4" bolt** and locknut (included). Slide has heavy welded SS ring for downhaul attachment. SS Slide is 3" long x 1 1/2" wide. As used on some **O'Day 25's, and others.**

SS Gooseneck Slide for 1 1/4" x 3/16" Flat Track & 1 1/2" Toggle: K-10430M:

Special SS Gooseneck Slide specially designed for use with Kenyon [K-10345-series](#) Gooseneck Toggle/Tack Assemblies. Slide fits 1 1/4" x 3/16" SS Flat Track (and Kenyon 1 1/4" Gooseneck Track, as well as standard 1 1/4" aluminum T-Track). SS Gooseneck Slide is 4" high x (maximum) 1 1/2" wide and fits most 1 1/2" Toggles using a **3/8" vertical pin or bolt**. Slide has heavy welded SS ring for attachment of downhaul line or shackle. As used on some **Hunter 33's, and others.**

**K-10430M*****Bronze Gooseneck Slide for 1 1/4" x 3/16" Flat Track & 2 1/2" Toggle: Mer 4150-311B:***

Chromed Bronze Gooseneck Slide fits 1 1/4" x 3/16" SS or Bronze Flat Track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 1/2" high with a **1/2" SS clevis pin** (included). Slide features recess underneath for use where Sailtrack (up to 5/8") is mounted on top of the Gooseneck Slide Track. Slide has integral loop for downhaul attachment and is 4" long x 1 7/8" wide.

Bronze Gooseneck Slide for 1 1/2" x 3/16" Flat Track & 2 1/2" Toggle: Mer 4150-321B:

Bronze Gooseneck Slide fits 1 1/2" x 3/16" SS or Bronze Flat Track. Cast Slide accepts a variety of Gooseneck Toggles up to 2 1/2" high with a **1/2" SS clevis pin** (included). Slide features recess underneath for use where Sailtrack (up to 7/8") is mounted on top of the Gooseneck Slide Track. Slide has integral loop for downhaul attachment and is 4" long x 1 7/8" wide.

Bronze Gooseneck Slide for 1 1/2" x 1/4" Flat Track & 2 3/8" Toggle: Fam 1309SA:

Bronze Gooseneck Slide fits 1 1/2" x 1/4" SS or Bronze Flat Track. Heavy Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a **1/2" SS clevis pin** (included). Slide features recess underneath for use where Sailtrack (up to 7/8") is mounted on top of the Gooseneck Slide Track. Slide has integral loop for downhaul attachment and is 4 1/2" long x 2 1/8" wide.

Bronze Gooseneck Slide for 2" x 1/4" Flat Track & 3 3/8" Toggle: Fam 1310SAB:

Bronze Gooseneck Slide fits 2" x 1/4" SS or Bronze Flat Track. Heavy Cast Slide accepts a variety of Gooseneck Toggles up to **3 3/8" high** with a **5/8" SS clevis pin** (included). Slide features recess underneath for use where Sailtrack (up to 1") is mounted on top of the Gooseneck Slide Track. Slide has integral loop for downhaul attachment and is 6 3/8" long x 2 9/16" wide.
*



Bronze Gooseneck Slide for 2" x 5/16" Flat Track & 2 3/8" Toggle: Fam 1310SAC:

Chrome Bronze Gooseneck Slide fits 2" x 5/16" SS or Bronze Flat Track. Heavy Cast Slide accepts a variety of Gooseneck Toggles up to 2 3/8" high with a **1/2" SS clevis pin** (included). Slide features recess underneath for use where Sailtrack (up to 1") is mounted on top of the Gooseneck Slide Track. Slide has integral loop for downhaul attachment and is 4 1/2" long x 2 1/2" wide.

Special Gooseneck Slides

Gooseneck Slide for 7/8" Internal SS "C" Track: K-R511S:

Special Gooseneck Slide to fit Nicro-Fico and Ronstan 7/8" SS "C" Track.

Die-cast chromed Bronze assembly includes **1/4" Vertical Pin** for attachment of Gooseneck Toggle up to 1 1/16" High. Slide features Spring Pin stop which is able to be locked in either up or down position, and has 3/16" hole for optional downhaul attachment. Slide is 3 1/4" long x (maximum) 7/8" wide. Commonly used with Gooseneck Toggle, Tack and Yoke Assembly, [K-10604](#). As used on Etchells 22. RF511SX



K-R511S

Proctor Spars Gooseneck Slides

Small Slide & Gooseneck Ass'y for Proctor Standard Boom: PRS 89-40ASG:

Special Small SS Gooseneck Slide Assembly to fit Proctor Dingy Masts with unmodified track, and Booms with standard 1/2" Square hole in boom end. Investment Cast SS Assembly features large captive Thumbscrew to allow for quick Boom height adjustment. Slide is (maximum) 2 13/16" long x 5/8" (.600") wide. Waist is 5/32" wide x (minimum) 1/8" high.

Wide Slide & Gooseneck Ass'y for Proctor Standard Boom: PRS 89-44AWB:


Gooseneck Slide Assembly to fit Proctor Dingy Masts where integral Track has been spread to 5/8" wide, and Booms with standard 1/2" Square hole in boom end. Investment Cast SS Assembly features **Ball & Socket Toggle** arrangement and large Thumbscrew to allow for quick Boom height adjustment. Slide is (maximum) 2 7/8" long x 7/8" (.850") wide. Waist is 9/16" wide x 1/4" (.240") high. asg



PRS 89-44AWB

Wide Slide & Gooseneck Ass'y for Proctor Standard Boom: PRS 89-45AWH:

Gooseneck Slide Assembly to fit Proctor Dingy Masts where integral Track has been spread to 5/8" wide, and Booms with standard 1/2" Square hole in boom end. Investment Cast SS Assembly features **Special Heavy-Duty Toggle** for maximum articulation and large Thumbscrew to allow for quick Boom height adjustment. Slide is (maximum) 3" long x 7/8" (.850") wide. Waist is 9/16" wide x 1/4" (.240") high. asg



PRS 89-45AWH

Wide Gooseneck Slide for Proctor Roller Reefing Boom: PRS 89-47SWRR:

Gooseneck Slide to fit Proctor Dingy Masts where integral Track has been spread to 5/8" wide, and Booms with special 5/8" Vertical Pin. Investment Cast SS Slide has welded 5/8" ID vertical tube to accept **Special Roller Reefing Boom** with 5/8" vertical attachment Pin. Slide features large Thumbscrew to allow for quick Boom height adjustment. Slide is

(maximum) 3 1/4" long x 7/8" (.850") wide. Waist is 9/16" wide x 1/4" (.240") high. ws



PRS89-47SWRR

SS Slide w/ Thumbscrew for Proctor 3/4" Internal Track: PRS 89-48ATS:

SS Gooseneck Slide to fit Proctor Masts with 3/4" internal flat track has Thumbscrew to lock it in place. Investment Cast SS Slide accepts a 3/4" high Toggle with a 3/8" vertical Pin. Slide is (maximum) 3" long x 3/4" (.748") wide. **Note:** Short waist is 7/16" (.455") wide x 1/8" (.145") high, and restricts usage on many Mast Sections.



PRS89-48ATS

SS Slide & Toggle Ass'y for Proctor 3/4" Internal Track: PRS 89-49AFT:

SS Gooseneck Slide and Toggle Assembly to fit Proctor Masts with 3/4" internal flat track, and Booms requiring a 3/4" wide Toggle with a 3/8" horizontal Pin. Investment Cast SS Slide has 3/8" vertical Pin with Shackles for Tack and downhaul, and 3/4" square x 1 3/4" long Aluminum Toggle with 3/8" horizontal Pin (included) to fit a variety of Proctor Booms. Slide is (maximum) 3" long x 3/4" (.748") wide. **Note:** Short waist is 7/16" (.455") wide x 1/8" (.145") high, and restricts usage on many Mast Sections.
ats



PRS 89-49AFT

~ [Back to Spars Main Page](#) ~

~ [Back to Rig-Rite Home Page](#) ~